

# KP-CF(M)

## KEEN Control Duty Floats



**“KP-CF10”** (10 Ft. Lg)  
 Mercury Float.....CONTROL PILOT DUTY  
 Narrow Angle Operation  
 Normally Open w/Cord (10’,15’,20’,30’,50’ Options)  
 18/2 SJOW-A Cord w/External Weight  
 2 Amp @ 120VAC

**“KP-CF10M”** (10 Ft. Lg)  
 Mechanical Float.....CONTROL PILOT DUTY  
 Narrow Angle Operation  
 Normally Open w/Cord (10’,15’,20’,30’,50’ Options)  
 18/2 SJOW-A Cord w/External Weight  
 2 Amp @ 120VAC

**Construction: (All Floats)**

<b><i>Outer Shell</i></b>	ABS (Acrylonitril Butadiene Styrene), rated 105 deg. C, ultrasonically welded
<b><i>Mercury Switch</i></b>	Hermetically welded and sealed canister pressurized pure argon gas for mercury Provides clean, spark extinguishing atmosphere for long life
<b><i>Mechanical Switch</i></b>	Snap-action switch, steel ball in switching tube
<b><i>Cord</i></b>	Flexible SJOW in lengths to 50’ Epoxy potted and bonded to float for watertight seal
<b><i>Weights</i></b>	Provided (attached) with all float controls