



- Discharge:** 2" NPT, female, vertical.
- Spherical SLD HNDLG:** 2"
- Liquid temperature:** 104°F (40°C) max.
- Volute:** Cast iron ASTM A-48 class 30.
- Motor housing:** Cast iron ASTM A-48 class 30.
- Impeller:** Vortex. Cast iron ASTM A-48 class 30, dynamically balanced, ISO G6.3.
- Shaft:** 416 series stainless steel.
- O-rings:** Square shaped Buna-N.
- Paint:** Air dry enamel, water based.
- Seal:** Single mechanical, oil filled chamber. Carbon / Ceramic / Buna-N, with stainless steel hardware.
- Hardware:** 300 series stainless steel.
- Cord entry:** 30 ft of neoprene cord SJTOW 16/3, sealed against moisture.
- Upper bearing:** Ball, single row, oil lubricated, for radial loads.
- Lower bearing:** Ball, single row, oil lubricated, for radial and axial loads.
- Motor:** NEMA L, single phase, permanent split capacitor, 115 volts, 60 Hz, 3500 RPM, oil filled, with overload protection in motor.
- Optional Equipment:** Additional cord, slide rail coupling (SRC-2).

MODEL	HP	VOLTS	PHASE	RPM	MAX AMPS	LOCKED ROTOR AMPS	CORD SIZE	CORD TYPE	WEIGHT (POUNDS)
K2PLSEV512	0.5	115	1	3500	10.2	16	16/3	SJTOW	51
K2PLSEV512A	0.5	115	1	3500	10.2	16	16/3	SJTOW	53
K2PLSEV512F	0.5	115	1	3500	10.2	16	16/3	SJTOW	53

A = Automatic Float Switch, VF = Automatic Vertical Float Switch

