


PUMP SERIES	K14VK		14" SUBMERSIBLE SEWAGE PUMPS		
Speed	1750 RPM	Discharge	14"	Solids	6"

GPM: \_\_\_\_\_ TDH: \_\_\_\_\_

### Performance




The curves reflect maximum performance characteristics without exceeding full load. Operation is recommended in the bounded area with operational point within the curve limit. Performance curves are based on actual tests with clear water at 70° F and 1280 feet site elevation.



PUMP SERIES	K14VK		14" SUBMERSIBLE SEWAGE PUMPS		
Speed	1150 RPM	Discharge	14"	Solids	6"

GPM: \_\_\_\_\_ TDH: \_\_\_\_\_

### Performance




The curves reflect maximum performance characteristics without exceeding full load. Operation is recommended in the bounded area with operational point within the curve limit. Performance curves are based on actual tests with clear water at 70° F and 1280 feet site elevation.

PUMP SERIES	K14VK		14" SUBMERSIBLE SEWAGE PUMPS		
Speed	870 RPM	Discharge	14"	Solids	6"

GPM: \_\_\_\_\_ TDH: \_\_\_\_\_

## Performance



The curves reflect maximum performance characteristics without exceeding full load. Operation is recommended in the bounded area with operational point within the curve limit. Performance curves are based on actual tests with clear water at 70° F and 1280 feet site elevation.