



- Discharge:** 2" NPT, female, vertical.
- Liquid temperature:** 104°F (40°C) Continuous
- Volute:** Cast iron ASTM A-48 class 30.
- Motor housing:** Cast iron ASTM A-48 class 30.
- Impeller:** Cast Iron ASTM A-48, Class 30, 2 Vane open with pump out vanes on back side.
- Shaft:** 420 Stainless Steel.
- O-rings:** Buna-N.
- Seal:** Single Seal, Carbon/Ceramic
Elastomer - Buna -N
- Hardware:** 300 series stainless steel.
- Cord entry:** 20 Ft Cord w/Plug, UL & CUL 14AWG, Type SJTOW
- Upper bearing:** Ball, single row, oil lubricated, for radial loads.
- Lower bearing:** Ball, single row, oil lubricated, for radial and axial loads.
- Motor:** Single Phase, 1750 RPM, 60 Hz, 115V, 12A; 230V, 6A, Includes Overload Protec on in, the motor, Oil Filled, Class B, Capacitor Start / Capacitor Run
- Switch Type:** Piggy-back Float Switch

MODEL	HP	VOLTS	PH/HZ	RPM	AMPS	SWITCH TYPE	DISCHARGE SIZE	CORD TYPE	CORD LENGTH	WEIGHT (POUNDS)
KW-52	1.5	230	1/60	1750	6	Manual	2"	SJTOW	20'	49
KW-52A	1.5	230	1/60	1750	6	Teathered Automatic	2"	SJTOW	20'	50

