

<b>Discharge:</b>	2" NPT, female, vertical.
<b>Liquid temperature:</b>	104°F (40°C) Continuous
<b>Volute:</b>	Cast iron ASTM A-48 class 30.
<b>Motor housing:</b>	Cast iron ASTM A-48 class 30.
<b>Seal Plate:</b>	Cast iron ASTM A-48 class 30.
<b>Impeller:</b>	Cast Iron ASTM A-48, Class 30, 2 Vane open with pump out vanes on back side.
<b>Shaft:</b>	420 Stainless Steel.
<b>O-rings:</b>	Buna-N.
<b>Seal:</b>	Dual Mechanical Seals (Motor Side) Rotating Face - Carbon, Stationary Face - Ceramic (Pump Side) Rotating Face - Silicon Carbide, Stationary Face - Silicon Carbide
<b>Hardware:</b>	300 series stainless steel.
<b>Cord entry:</b>	20 Ft Cord With Pressure Grommet for Sealing, UL listed SJTOW
<b>Upper bearing:</b>	Ball, single row, oil lubricated, for radial loads.
<b>Lower bearing:</b>	Ball, single row, oil lubricated, for radial and axial loads.
<b>Motor:</b>	Single Phase, 3450 RPM, 115V, 60 Hz. Includes Overload Protection in the motor, Oil Filled, Class B, Capacitor Start / Capacitor Run
<b>Switch Type:</b>	Piggy-back Float Switch

MODEL	HP	VOLTS	PHASE	RPM	FULL LOAD AMPS	LOCKED ROTOR AMPS	CORD SIZE	CORD TYPE	WEIGHT (POUNDS)
K5SDS	0.5	115/127	1/60	3450	10	37	14/3	SJTOW	57
K7SDS	0.75	115/127	1/60	3450	12	45	14/3	SJTOW	58
K10SDS	1	115/127	1/60	3450	15	45	14/3	SJTOW	59

